




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B60G 3/26		A1	(11) International Publication Number: WO 95/15865
			(43) International Publication Date: 15 June 1995 (15.06.95)
(21) International Application Number: PCT/KR94/00174 (22) International Filing Date: 8 December 1994 (08.12.94) (30) Priority Data: 1993/27181 10 December 1993 (10.12.93) KR 1993/27185 10 December 1993 (10.12.93) KR (71) Applicant (for all designated States except US): HYUNDAI MOTOR COMPANY [KR/KR]; 140-2, Kye-dong, Jongro-ku, Seoul 110-270 (KR). (72) Inventor; and (75) Inventor/Applicant (for US only): LEE, Un, Koo [KR/KR]; 5-808, Miryung Apartment, Bisan 2-dong, Anyang-si, Kyungki-do 430-050 (KR). (74) Agents: KIM, Won, Ho et al.; You Me Patent & Law Firm, 702, Teheran Boulevard, 825-33, Yoksam-dong, Kangnam-ku, Seoul 135-080 (KR).			(81) Designated States: CA, JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: SUSPENSION SYSTEM FOR VEHICLE

(57) Abstract

The present invention relates to a suspension system which can enhance driving safety and margin cornering performance by optimally controlling the camber and thread changes as well as roll center in accordance with vehicle's driving conditions. The suspension system includes a wheel carrier (1) supporting a wheel (2) and having upper and lower ends, a lower control arm (5) connecting the lower end of said wheel carrier (1) to a vehicle body, an upper control arm (3) for connecting the upper end of the wheel carrier (1) to the vehicle body, and a strut assembly (7) formed by uniting a shock absorber (71) and a spring (72) to absorb an up-and-down vibration of the vehicle body, and a camber control member (9) provided for controlling the camber of the wheel by pushing the lower control arm (5) to a wheel side and pulling the upper control arm (3) to a vehicle body side when the wheel pumps or rebounds, the camber control member (9) including first, second and third hinge points connected to the respective one of the upper control arm (3), lower control arm (5) and the strut assembly (7).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MD	Republic of Moldova	TJ	Tajikistan
DE	Germany	MG	Madagascar	TT	Trinidad and Tobago
DK	Denmark	ML	Mali	UA	Ukraine
ES	Spain	MN	Mongolia	US	United States of America
FI	Finland			UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

SUSPENSION SYSTEM FOR VEHICLE**BACKGROUND OF THE INVENTION****5 Field of the Invention**

10 The present invention relates to a suspension system for a vehicle and, more particularly, to the suspension system which can enhance driving safety and marginal cornering performance by optimally controlling the camber and tread changes as well as roll center in accordance with vehicle's driving conditions.

Description of Related Art

15

20 In general, the primary functions of a suspension system are to (A) provide vertical compliance so wheels can follow the uneven road, isolating a vehicle body from roughness in the road, (B) maintain the wheels in the proper steer and camber attitudes to the road surface, and (C) react to the control forces produced by the tires-longitudinal (acceleration and braking) force, lateral(cornering) forces, and braking and driving torques, (D) resist roll, yaw and pitch of the vehicle
25 body.

30 The suspension system is structurally characterized as solid axle and independent suspension types. The suspension system of the present invention concerns the independent suspension system. There are MacPherson strut type and Wishbone type suspension systems in the independent suspension systems. And in recent year, a multi-link type independent suspension system has been popular.

35

FIG. 6A illustrates a general MacPherson strut type

suspension system which comprises a strut assembly 155 formed by uniting a shock absorber 151 and a spring 152 and having a lower end fixed to a wheel carrier 153 rotatably supporting a wheel 150 and an upper end supportably connected to a vehicle body 154; and a lower control arm 156 connecting a lower end of the wheel carrier 153 to a lower side of the vehicle body 154.

The range of a wheel's up-and-down movement in this suspension system is determined by the lower control arm 156 during a wheel's up-and-down vibration. The vibration is absorbed by an elastic bushing formed on an inner end of the lower control arm. Shock from a road surface is absorbed by the shock absorber 151 and spring 152 of the strut assembly 155.

However, when considering operation steps of the above described suspension system, if the wheel 150 vibrates upward and downward in accordance with driving conditions, the wheel 150 moves upward and downward in a state where the length of the lower control arm 156 is fixed.

Accordingly, the wheel 150 moves upward and downward along a tracing movement M which is formed by the length of lower control arm 156. A camber and a tread are changed according to the wheel's up-and-down movement and has a great effect on riding comfort, cornering performance, and driving safety of the vehicle.

That is, since the outer end of the lower control arm 156 is designed to be lower than the wheel center, when the wheel moves along the tracing movement M, in a normal ascending section, the lower side of the wheel is pushed outward, that is, to the wheel side, along a

curvature of the tracing movement M such that the camber is changed to negative(-).

5 However, in a section over the normal ascending section, the lower control arm 156 ascends and pulls the lower side of the wheel to the vehicle body side, whereby the camber is changed again to positive(+) (See broken line of FIG. 4A).

10 The change of the camber as described above is illustrated in broken line of FIG. 4A. Further a tread is changed as illustrated in broken line of FIG. 4B by the change of the camber described above. Such changes of the camber and tread have a bad effect on the
15 cornering performance and the straight-ahead driving safety.

 FIG. 6B illustrates a general Wishbone type suspension system, including upper and lower control
20 arms 61 and 62, a steering knuckle 63, a spring assembly 65 including a shock absorber 64, and ball joints 66 and 67 respectively connecting the upper and lower control arms 61 and 62 to the steering knuckle 63.

25 This type of suspension system has a problem that when the wheel 69 moves upward and downward, since the upper control arm 61 has a small curvature tracing movement and the lower control arm 62 has a large curvature tracing movement, the tread and camber are
30 severely changed(See dot-dash line of FIGS. 4A and 4B).

 Further, as shown in broken line of FIG. 5, in the Wishbone and Macpherson type suspension systems, when the vehicle is cornering, the more wheel on the outer
35 side of turn to receive the lateral force, the more camber is changed to the positive(+), thereby

deteriorating the marginal cornering performance.

SUMMARY OF THE INVENTION

5 Accordingly, the present invention has been made in an effort to solve the above-described problems.

10 It is an object of the present invention to provide a suspension system which can ideally control the camber and the tread through a movement range of the wheel, that is, the range from the bump to rebound, thereby improving marginal cornering performance, driving safety and riding comfort.

15 To achieve the above object, the present invention provides a suspension system for a vehicle, comprising: a wheel carrier supporting a wheel, said wheel carrier having upper and lower ends; a lower control arm connecting the lower end of said wheel carrier to a vehicle body; an upper control arm for connecting the upper end of said wheel carrier to the vehicle body; and a strut assembly formed by uniting a shock absorber and a spring to absorb an up-and-down vibration of the vehicle body; wherein means are provided for controlling the camber of the wheel by pushing said lower control arm to a wheel side and pulling the upper control arm to a vehicle body side when the wheel pumps or rebounds, said means including first, second and third hinge points connected to the respective one of said upper control arm, lower control arm and the strut assembly.

35 As an aspect of the present invention, said means for controlling includes a hinge portion pivotally connected to said lower control arm to thereby form the first hinge point, a horizontal arm extending toward the vehicle body side from the hinge portion, and a vertical

arm extending from the hinge portion toward said upper control arm and pivotally connected to said upper control arm to thereby form the second hinge point, and wherein said strut assembly having an upper end supportably connected to the vehicle body and a lower end pivotally connected to an inner end of the horizontal arm of said means to thereby form the third hinge point.

10 As another aspect of the present invention, said means for controlling includes a hinge portion pivotally connected to said upper control arm to thereby form the first hinge point, a horizontal arm extending from the hinge portion toward the vehicle body, and a vertical arm extending from the hinge portion toward said lower control arm and pivotally connected to said lower control arm to thereby form the second hinge point, and wherein said strut assembly having an upper end supported to the vehicle body and a lower end pivotally connected to an inner end of the horizontal arm of said means for controlling to thereby form the third hinge point.

BRIEF DESCRIPTION OF THE DRAWINGS

25 The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus, are not limitative of the present invention, and wherein:

FIG. 1 is a perspective view of a suspension system in accordance with a first embodiment of the present invention;

35 FIG. 2 is a schematic front view illustrating an

operating state of the suspension system in FIG. 1;

FIG. 3 is a perspective view of a suspension system in accordance with a second embodiment of the present invention;

FIG. 4A is a graph for comparing a camber change between the suspension system of the present invention and conventional suspension systems;

FIG. 4B is a graph for comparing a tread change between a suspension system of the present invention and conventional suspension systems;

FIG. 5 is a graph illustrating a camber change in response to a lateral force of a suspension system of the present invention compared to conventional suspension systems;

FIG. 6A is a view illustrating a conventional MacPherson type suspension system; and

FIG. 6B is a view illustrating a conventional Wishbone type suspension system.

DETAILED DESCRIPTION OF THE EMBODIMENT

FIG. 1 illustrates a suspension system in accordance with a first embodiment of the present invention. The suspension system includes a wheel carrier 1 rotatably supporting a wheel(not shown), an upper control arm 3 connecting the upper end of the wheel carrier 1 to a vehicle body(not shown), a lower control arm 5 connecting the lower end of the wheel carrier 1 to the vehicle body, a strut assembly 7 formed by uniting a shock absorber 71 and a spring 72, and a

camber control member 9 interconnecting the upper and lower control arms 3 and 5.

5 The upper control arm 3 includes first and second control arms 31 and 32 both of which are of Y-shaped construction. The first control arm 31 is attached at its outer end to the wheel carrier 1 by means of a ball joint 310 and has front and rear links 311 and 312 diverging from the outer end. Bushings 313 and 314 are
10 formed on the inner ends of each front and rear link 311 and 312, respectively, and are pivotally coupled with a bushing 320 formed on the outer end of the second control arm 32 by means of a pin 33 to thereby form a moving hinge point H1. The second control arm 32 has
15 front and rear links 321 and 322 which diverge from its outer end provided with the bushing 320 and are mounted at their inner ends to the vehicle body by means of bushings 323 and 324 that allow up and down movement of the outer end of the second control arm 32.

20

The lower control arm 5 is also of Y-shaped construction and attached at its outer end to the wheel carrier 1 by a ball joint 51. The lower control arm 5 has front and rear links 52 and 53 mounted at their
25 inner ends to the vehicle body by means of bushings 521 and 522, respectively.

Each bushing 323, 324 and 521, 522 has an elastic force to control the up and down movement of the
30 respective upper and lower control arms 3 and 5.

The camber control member 9 connecting the lower control arm 5 to the upper control arm 3 includes a hinge portion 91 pivotally coupled by a pin 911 to a
35 bracket 94 integrally mounted on an upper surface of the lower control arm 5 thereby forming a hinge point H2, a

8

pair of horizontal arms 92 integrally extending from the hinge portion 91 to the vehicle body side, and a pair of vertical arms 93 integrally extending from the hinge portion 91 upward and pivotally coupled to the first control arm 31 of the upper control arm 3 by respective pins 931 thereby forming a hinge point H3.

The strut assembly 7 for absorbing a shock transmitted to the vehicle body in the up-and-down direction is connected at its upper end to a vehicle body by means of an insulator 73 and at its lower end to a pair of bushings 921 formed on the inner ends of the horizontal arms 92 of the camber control member 9 by respective pins 922 to thereby form a hinge point H4.

15

FIG. 2 illustrates an operating state of the above described suspension system.

When the wheel 2 receives force F1 from an uneven road or during cornering to thereby bump, the force F1 is absorbed by the strut assembly 7 and, at the same time the inner end of the horizontal arm 92 pivotally connected to the lower end of the strut assembly 7 receives a reacting force F2 of the spring 72 such that the camber control member 9 rotates in the counter-clockwise direction on the basis of the hinge point H2 in the drawing.

Accordingly, the force F2 acts as force F3 which pushes the lower control arm 5 connected to the camber control member 9 outward such that the wheel bumps while pulling the bushings 521 and 522 of the lower control arm 5 to the wheel side by using an elasticity of these bushings 521 and 522.

35

At this point, since the camber control member 9

rotates in the counter-clockwise direction, the first control arm 31 on which the upper end of the vertical arm 93 of the camber control member 9 is connected receives a force F_4 which pushes the first control arm 31 inward and upward. As a result, the first control arm 31 pulls the upper end of the wheel carrier 1 to the vehicle body side while the hinge point H1 on which the first and second control arms are connected with each other moves upward.

10

As described above, the lower end of the wheel carrier 1 is pushed to the outer side, that is, the opposite side of the vehicle body, and the upper end of the wheel carrier 1 is pushed to the inner side, that is, the vehicle body side. Accordingly, when the wheel 2 is in bump or rebound, as shown in dot-dash line of FIG. 2, the camber angle α is changed to negative(-).

15

The change of the camber as described above is illustrated in solid line of FIG. 4A. That is, the camber of the present invention is changed to negative(-) linearly compared to the camber change of the conventional art.

20

Further the tread is changed as illustrated in solid line of FIG. 4B by the camber change of the present invention described above. That is, the tread is slightly changed to positive(+) linearly.

25

Accordingly, when the vehicle is in a straight ahead position, since a few change of camber occurs, straight ahead driving safety is greatly improved as well as riding comfort.

30

FIG. 3 illustrates a suspension system in accordance with a second embodiment of the present

35

10

invention, which can be applied to the drive wheel. In this embodiment, the same elements as those in the previously described embodiment are designated by the same reference numerals and the description thereof will be omitted for simplicity.

In this embodiment, the structures of upper and lower control arms are the same as those of the first embodiment but the connecting structure of the camber control member is modified to accept a drive shaft.

That is, as shown in FIG. 3, a camber control member 8 connecting the lower control arm 5 to the upper control arm 3 includes a hinge portion 81 pivotally connected to the first control arm 31 by means of a pin 831 to thereby form a hinge point P1, a horizontal arm 82 integrally extending from the hinge portion 81 inward and downward, and a vertical arm 83 integrally extending downward from the hinge portion 81 and pivotally fixed to a bracket 84 formed on the upper surface of the lower control arm 5 by a pin 811 to thereby form a hinge point P2.

The strut assembly 7 for absorbing a shock transmitted to the vehicle body in the up-and-down direction is connected at its upper end to the vehicle body by means of the insulator 73 and at its lower end with a bushing 821 formed at the inner end of the horizontal arm 82 of the camber control member 8 by a pin 822, pivotally, thereby forming a hinge point P3.

Further, the vertical arm 83 is provided with a hole 85 through which the drive shaft(not shown) can be penetrated.

35

According to this embodiment, when the wheel

receives force F_1 from the uneven road or during cornering to thereby bump, the force F_1 is absorbed by the strut assembly 7 and, at the same time the inner end of the horizontal arm 82 connected to the lower end of the strut assembly 7 receives a reacting force F_2 of the spring 72 such that the camber control member 8 rotates in the counter-clockwise direction on the basis of the hinge point P_1 when viewed from the drawing.

Accordingly, the force F_2 acts as a force F_3 which pushes the lower control arm 5 coupled to the camber control member 8 to the wheel side such that the wheel ascends while pulling the inner end of the lower control arm 7 to the wheel side by using an elasticity of the bushings 821 and 822.

Further, since the camber control member 8 rotates in the counter-clockwise direction, the first control arm 31 receives force F_4 which pushes the first control arm 31 inward. As a result, the first control arm 31 pulls the upper end of the wheel carrier to the vehicle side while the hinge point P_4 where the first and second control arms 31 and 32 connected with each other moves upward.

The camber and tread changes of the suspension system according to the second embodiment are the same as those in the previously described embodiment and the description thereof is omitted.

In the suspension systems of each first and second embodiment of the present invention as described above, when the vehicle is cornering, the camber in response to the lateral force of the wheel on the outer side of the turn is maintained regularly as shown in solid line of FIG. 5.

12

The suspension system of the present invention is designed such that the reacting force F_2 is changed into forces F_3 and F_4 when the wheel bumps or rebounds by an uneven road or during cornering, whereby the wheel (on the outer side of the turn) is changed to negative(-) camber by a force-compliance. Particularly, the suspension system prevents the wheel on the outer side of the turn from being changed to positive(+) camber such that the margin cornering performance is improved by increasing a grip force of a tire.

Although preferred embodiments of the present invention have been described in detail hereinabove, it should be clearly understood that many variations and/or modifications of the basic inventive concepts herein taught which may appear to those skilled in the pertinent art will still fall within the spirit and scope of the present invention, as defined in the appended claims.

WHAT IS CLAIMED IS:

1. A suspension system for a vehicle, comprising:

5 a wheel carrier supporting a wheel, said wheel carrier having upper and lower ends;

a lower control arm connecting the lower end of said wheel carrier to a vehicle body;

10 an upper control arm for connecting the upper end of said wheel carrier to the vehicle body;

15 a strut assembly formed by uniting a shock absorber and a spring to absorb an up-and-down vibration of the vehicle body; and

20 means for controlling the camber of the wheel by pushing said lower control arm to a wheel side and pulling the upper control arm to a vehicle body side when the wheel pumps or rebounds, said means for controlling including first, second and third hinge points connected to the respective one of said upper control arm, lower control arm and the strut assembly.

25 2. The suspension system according to claim 1, wherein said means for controlling includes a hinge portion pivotally connected to said lower control arm to thereby form the first hinge point, a horizontal arm
30 extending toward the vehicle body side from the hinge portion, and a vertical arm extending from the hinge portion toward said upper control arm and pivotally connected to said upper control arm to thereby form the second hinge point, and wherein said strut assembly
35 having an upper end supportably connected to the vehicle body and a lower end pivotally connected to an inner end

14

of the horizontal arm of said means to thereby form the third hinge point.

3. The suspension system according to claim 1,
5 wherein said means for controlling includes a hinge portion pivotally connected to said upper control arm to thereby form the first hinge point, a horizontal arm extending from the hinge portion toward the vehicle body, and a vertical arm extending from the hinge
10 portion toward said lower control arm and pivotally connected to said lower control arm to thereby form the second hinge point, and wherein said strut assembly has an upper end supported to the vehicle body and a lower end pivotally connected to an inner end of the
15 horizontal arm of said means, for controlling to thereby form the third hinge point.

4. The suspension system according to claim 2,
wherein said upper control arm includes a first control
20 arm to which the vertical arm of said means for controlling is pivotally connected, and a second control arm is pivotally connected to the first control arm.

5. The suspension system according to claim 3,
25 wherein the upper control arm comprises a first control arm to which the hinge portion of said means for controlling is pivotally connected, and a second control arm is pivotally connected to the first control arm.

30 6. The suspension system according to claim 1, wherein one ends of each upper and lower control arm are connected with the vehicle body by a bushing and the other ends of each upper and lower control arm are connected with the wheel carrier by a ball joint.

35

7. The suspension system according to claim 3,


wherein the vertical arm of said means for controlling is provided with a hole through which a drive axle can be penetrated.

5 8. The suspension system according to claim 4, wherein the first and second arms are interconnected by interposing a bushing.

10 9. The suspension system according to claim 5, wherein the first and second arms are interconnected by interposing a bushing.


1/7

FIG. 1




2/7

FIG.2



3/7

FIG.3



4/7

FIG.4A






FIG.4B




5/7

FIG.5




6/7

FIG.6A Conventional Art



7/7

FIG.6B Conventional Art



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR 94/00174

A. CLASSIFICATION OF SUBJECT MATTER

IPC⁶: B 60 G 3/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁶: B 60 G 3/00, 3/18, 3/20, 3/26

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 13 63 520 A (STAMMREICH) 14 August 1974 (14.08.74), totality.	1
X	US 49 27 169 A (SCADUTO) 22 May 1990 (22.05.90), totality.	1
A	GB 22 08 216 A (FUJI) 15 March 1989 (15.03.89), fig.1.	1,3,5
A	EP 05 06 141 A1 (YAMAHA) 30 September 1992 (30.09.92), fig. 1,2,7,8,9.	1
A	WO 91/08 918 A1 (YOROZU) 27 June 1991 (27.06.91), totality.	1
A	US 52 57 801 A (MATSUZAWA) 02 November 1993 (02.11.93), fig. 1-13D.	1

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

02 March 1995 (02.03.95)

Date of mailing of the international search report

09 March 1995 (09.03.95)

Name and mailing address of the ISA/ AT
 AUSTRIAN PATENT OFFICE
 Kohlmarkt 8-10
 A-1014 Vienna
 Facsimile No. 1/53424/535

Authorized officer

Pangratz e.h.

Telephone No.

1/53424/413

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR 94/00174

Im Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
GB A 1363520	14-08-74	US A 3711113	16-01-73
US A 4927169		keine - none - rien	
GB A 2208216		DE A1 3823600	26-01-89
		GB A0 8816528	17-08-88
		GB A1 2208216	15-03-89
		GB B2 2208216	05-06-91
		JP A2 1018710	23-01-89
		US A 4842297	27-06-89
EP 506141		JP A2 4297311	21-10-92
		CA AA 2064278	30-09-92
		EP A1 506141	30-09-92
WO A1 9108918	27-06-91	DE U1 9090175	19-03-92
		DE T 4092219	23-04-92
		JP A2 3213414	18-09-91
		US A 5284353	08-02-94
		JP A2 3213413	18-09-91
		JP A2 3213412	18-09-91
		JP A2 3213411	18-09-91
		JP A2 3213410	18-09-91
		JP A2 3186410	14-08-91
US 5257801		keine - none - rien	